

UNITED STATES PATENT APPLICATION FOR


DERIVING A GENOME REPRESENTATION
FOR EVOLVING GRAPH STRUCTURE WEIGHTS

Inventors:
Evan Kirshenbaum
Kenneth Stanley
Bin Zhang

CERTIFICATE OF MAILING BY "EXPRESS MAIL"
UNDER 37 C.F.R. § 1.10

"Express Mail" mailing label number: EI560987412US
Date of Mailing: 5-2-2001

I hereby certify that this correspondence is being deposited with the United States Postal Service, utilizing the "Express Mail Post Office to Addressee" service addressed to **Assistant Commissioner for Patents, Washington, D.C. 20231** and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.



Paul H. Horstmann, Reg. No. 36,167
Signature Date: 5-2-2001

00047869-0502001

BACKGROUND OF THE INVENTION

Field of Invention

5 The present invention pertains to the field of
designing graph structures. More particularly, this
invention relates to deriving a genome representation
for evolving the weights in a graph structure.

Art Background

10 A variety of disciplines including computer
science commonly express solutions to problems in the
form of graph structures. For example, neural
networks which are commonly used in computer-related
applications may be expressed in the form of graph
15 structures.

A graph structure typically includes a set of
nodes and a set of arcs that provide interconnections
among the nodes. Each arc of a graph structure
20 usually has an associated weight. The design of a
graph structure typically involves determining an
appropriate arrangement of nodes and arcs and
determining an appropriate weight for each arc.

25 One prior method for determining the weights in
a graph structure is to use genetic programming
techniques to evolve the weights. A typical genetic
programming method involves generating an initial
population of organisms each of which is a candidate
30 solution for the weights, selecting a subset of
organisms from the initial population for use as
parents of a generation of child organisms, and
generating the child organisms by combining genetic
material from the parent organisms using genetic

09847869 .050201
102050 .69847869

operators such as mutation and cross-over.
Typically, many generations of child organisms are
generated and tested before a suitable set of weights
is found.

5

The genetic operators of mutation and crossover
are usually applied to an arrangement of genetic
material which is commonly referred to as a genome
representation for the weights. It is usually
10 desirable to employ a genome representation that will
yield the most efficient evolution to a desired
solution. For example, a reduction in the number of
generations of organisms that are generated and
evaluated usually decreases the time it takes to
15 reach a desired solution and decreases the overall
design cost of a graph structure.

00047869 050204
T02050 69844860

SUMMARY OF THE INVENTION

5 A method is disclosed for deriving a genome
representation for the weights in a graph structure
that increases the likelihood that solutions to
substructures of the graph structure will be
preserved during crossover operations. The
preservation of solutions to substructures across
generations of organisms may decrease the time and
10 costs associated with evolving a suitable set of
weights.

15 A method for designing a graph structure
according to the present teachings includes
determining a genome representation for a set of
weights for a set of arcs in the graph structure such
that the arcs of the graph structure that participate
in a substructure of the graph structure are in a
close proximity in the genome representation. The
20 graph structure may then be evolved using the genome
representation.

25 Other features and advantages of the present
invention will be apparent from the detailed
description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is described with respect to particular exemplary embodiments thereof and
5 reference is accordingly made to the drawings in which:

Figure 1 shows a method for designing a graph structure which incorporates the present teachings;
10

Figures 2a-2b illustrate crossover operations which may be used to generate a child organism from a pair of parent organisms when evolving the graph structure;
15

Figure 3 shows one example of a graph structure which includes an arrangement of nodes and interconnecting arcs with associated weights.

DETAILED DESCRIPTION

Figure 1 shows a method for designing a graph structure which incorporates the present teachings.

5 At step 100, an arrangement of nodes and arcs for the graph structure is determined. Any one or more of a variety of known techniques may be employed at step 100 including designs by hand and automated methods.

10 At step 102, a genome representation for the weights of the graph structure from step 100 is determined. The genome representation is determined at step 102 such that the arcs of the graph structure that participate in a substructure of the graph
15 structure are in a close proximity in the genome representation. This arrangement for the genome representation increases the likelihood that the weights associated with a substructure will be preserved during the formation of a next generation
20 of organisms using crossover.

At step 104, the graph structure is evolved using the genome representation obtained at step 102. Step 104 may be performed using any one or more of a
25 variety of known genetic programming techniques.

Figures 2a-2b illustrate crossover operations which may be used at step 104 to generate a child organism from a pair of parent organisms when
30 evolving the graph structure 200. In this example, the parent and child organism each have genetic material made up of a sequence of bits.

Alternatively, the genetic material of an organism may be a sequence of numbers.

Figure 2a shows a one-point crossover operation 20 which combines a parent organism 30 with a parent organism 32 to yield a child organism 34. The one-point crossover operation 20 combines a sequence of genetic material 10010 from the parent organism 30 as a prefix with a sequence of genetic material 00100 from the parent organism 32 as a suffix to yield a sequence of genetic material 1001000100 in the child organism 34. The crossover point in this example is between the fifth locus and sixth locus of the sequence but in general may be located anywhere in the sequence. The locus of crossover may be randomly chosen each time.

Figure 2b shows a two-point crossover operation 22 which combines a sequence of genetic material 100----10 from the parent organism 30 with a sequence of genetic material 11001 from the parent organism 32 to yield a sequence of genetic material 1001100110 in the child organism 34. The crossover points in this example are between the third locus and fourth locus of the sequence and between the eighth locus and ninth locus of the sequence but in general may be located at any two positions in the sequence.

Figure 3 shows one example of a graph structure 200 which includes an arrangement of nodes 10-17 and interconnecting arcs which are referred to by their associated weights W1-W10. In one embodiment, the graph structure 200 represents a neural network.

09847869-050201
T02050-69824860

The example graph structure 200 includes a substructure of the arcs W1, W2, W5, and W6 and a substructure of the arcs W1, W2, W9, and W10 and a substructure of the arcs W3, W4, W7 and W8. A prior art breadth-first ordering of the weights W1-W10 of the graph structure 200 would result in the following sequence of genetic material in a genome representation.

10 W5 W6 W7 W8 W9 W10 W1 W2 W3 W4

This genome representation yielded by prior art techniques would break up the sequence of genetic material for the substructure of the arcs W1, W2, W5, and W6 when cross-over is applied between the first locus and the eighth locus. Similarly, the above genome representation yielded by prior art techniques would break up the sequence of genetic material for the substructure of the arcs W3, W4, W7 and W8 when cross-over is applied between the third locus and the tenth locus.

The breakup of this genetic material prevents possibly fit solutions for the substructure of the arcs W1, W2, W5, and W6 and for the substructure of the arcs W3, W4, W7 and W8 from being passed on to a next generation of organisms during evolution. Such a failure to pass on fit solutions can increase the time and cost associated with evolving the graph structure 200.

According to the present techniques, a genome representation is determined at step 102 by multiplying a connection matrix element-by-element

with a weight matrix to yield a product matrix. At
step 102, a score is generated by summing the
elements of the product matrix. A minimum value for
the score is determined at step 102 by exchanging and
the rows and columns of the connection matrix while
re-computing the score until a minimum value is
obtained. The connection matrix that yields the
minimum score provides the genome representation to
be used at step 104.

The connection matrix is generated such that
each row represents a node and each column represents
an arc, initially in some order. The value of an
element in the connection matrix is one if the node
represented by the row and the column represented by
the arc are connected and is zero otherwise.

The weight matrix is of the same size as the
connection matrix. Each element(i,j) of the weight
is given by the following equation:

$$element(i,j)=|D*i-N*j|$$

where D is the total number of columns, i.e. arcs,
and N is the total number of rows, i.e. nodes. The
value of an element of the weight matrix indicates an
amount by which the element is "off diagonal." For
example, if the number of rows is four and the number
of columns is four, the weight matrix is as follows.

0	4	8	12
4	0	4	8
8	4	0	4
12	8	4	0

Each cell of the weight matrix directly encodes the distance off the diagonal multiplied by the number of rows which is an immaterial constant factor. If the number of rows is three and the number of columns is five, the weight matrix is as follows.

0	3	6	9	12
2	2	1	4	7
10	7	4	1	5

10

The elements of the product matrix when summed equal a score which is lower when arcs that share nodes are closer together according to the linear ordering given by the row indices. The product matrix is iteratively generated by exchanging rows with other rows and columns with other columns so long as the score continues to diminish. In one embodiment, the score is determined for all exchanges of the first row with the other rows. This yields a locally optimal position for the weight referenced by the first row. The score is then determined for all exchanges of the second row with the other rows to yield a locally optimal position for the weight referenced by the second row, and so on. Thereafter, the score is determined for all exchanges of the first column with the other columns, then for all exchanges of the second column with the other columns, and so on. The product matrix having the lowest score yields an optimal arrangement of weights according to a metric which indicates proximity or compactness of weights associated with the same substructure.

15

20

25

30

09847869-05001
102050-59847869

For the example graph structure 200 having 8 nodes and 10 arcs, the weight matrix is as follows.

0	8	16	24	32	40	48	56	64	72
10	2	6	14	22	30	38	46	54	62
20	12	4	4	12	20	28	36	44	52
30	22	14	6	2	10	18	26	34	42
40	32	24	16	8	0	8	16	24	32
50	42	34	26	18	10	2	6	14	22
60	52	44	36	28	20	12	4	4	12
70	62	54	46	38	30	22	14	6	2

For the breadth-first ordering of the weights W1-W10 given by the sequence W5 W6 W7 W8 W9 W10 W1 W2 W3 W4, the connection matrix is as follows where N10-N17 refer to nodes 10-17, respectively.

	W5	W6	W7	W8	W9	W10	W1	W2	W3	W4
N10	1	1	1	1	0	0	0	0	0	0
N11	0	0	0	0	1	1	0	0	0	0
N12	1	0	0	0	1	0	1	0	0	0
N13	0	1	0	0	0	1	0	1	0	0
N14	0	0	1	0	0	0	0	0	1	0
N15	0	0	0	1	0	0	0	0	0	1
N16	0	0	0	0	0	0	1	1	0	0
N17	0	0	0	0	0	0	0	0	1	1

This yields the following product matrix.

		W5	W6	W7	W8	W9	W10	W1	W2	W3	W4
5	N10	0	8	16	24	0	0	0	0	0	0
	N11	0	0	0	0	22	30	0	0	0	0
	N12	20	0	0	0	12	0	28	0	0	0
	N13	0	22	0	0	0	10	0	26	0	0
	N14	0	0	24	0	0	0	0	0	24	0
	N15	0	0	0	26	0	0	0	0	0	22
10	N16	0	0	0	0	0	0	12	4	0	0
	N17	0	0	0	0	0	0	0	0	6	2

The score for this product matrix is 338.

15 The product matrix having the lowest score in this example is as follows.

		W5	W1	W2	W6	W7	W3	W8	W4	W9	W10
	N12	0	8	0	0	0	0	0	0	64	0
	N16	0	2	6	0	0	0	0	0	0	0
20	N13	0	0	4	0	12	0	0	0	0	52
	N10	30	0	0	6	2	0	18	0	0	0
	N14	0	0	0	0	8	0	0	0	0	0
	N17	0	0	0	0	0	10	0	6	0	0
	N15	0	0	0	0	0	0	12	4	0	0
25	N11	0	0	0	0	0	0	0	0	2	1

This product matrix yields a score of 247. The connection matrix that corresponds this product matrix having the lowest score is as follows.

	W5	W1	W2	W6	W7	W3	W8	W4	W9	W10
N12	1	1	0	0	0	0	0	0	1	0
N16	0	1	1	0	0	0	0	0	0	0
N13	0	0	1	0	1	0	0	0	0	1
N10	1	0	0	1	1	0	1	0	0	0
N14	0	0	0	0	1	1	0	0	0	0
N17	0	0	0	0	0	1	0	1	0	0
N15	0	0	0	0	0	0	1	1	0	0
N11	0	0	0	0	0	0	0	0	1	1

These product and connection matrices yield the following sequence of genetic material in an optimized genome representation according to the present teachings.

W5 W1 W2 W6 W7 W3 W8 W4 W9 W10

This linear sequence of weights provided by the optimized genome representation may be translated into a data structure representing the graph structure 200 in several ways. For example, the internal representation of the graph data structure may contain the appropriate index into the genome representation either directly or through a table indexed by an inherent link index. Whenever a weight is needed, this index is used to extract the correct number from the genome representation. In another example, a table may map the index in genome-order to the intrinsic index in the graph data structure. Before the graph structure is evaluated, this table is traversed and the weights from the genome are patched into the data structure.

In an alternative embodiment, the connection matrix is a square matrix whose rows and columns both represent arcs and whose elements hold a one if and only if the corresponding two arcs share a node in common. The corresponding weight matrix represents the true distance off the main diagonal. In this embodiment, the rows and columns are swapped at the same time, i.e. when swapping rows i and j columns i and j are also swapped, when finding the optimal score.

A variety of hardware systems including general purpose computer systems and specialized systems may be employed to automatically design a desired structure by deriving a genome representation according to the present teachings. The present techniques decrease the computational time on the hardware system employed to automatically determine the genome representation and automatically evolve the weights.

The foregoing detailed description of the present invention is provided for the purposes of illustration and is not intended to be exhaustive or to limit the invention to the precise embodiment disclosed. Accordingly, the scope of the present invention is defined by the appended claims.